



## Features

The FIP (fire indicator panel) incorporates:

- 2x Detection circuits;
- 1x Extinguishing Discharge circuit;
- 1x Siren/Strobe circuit;
- 1x Agent Release Notification circuit;
- Programmable Activation (automatic and/or manual);
- Fault Monitoring system;
- Isolation Function.
- Cable loom uses Deutsch plugs for "plug and Play" installation.
- Cables are colour coded for easy identification.



## General Information

The FirePro FP-08451 Fire Control Panel is a combined detection and extinguishant system, and is compliant for use in both marine (AMSA NSCV) and vehicle installations (AS5062).

The FP-08451 Control Panel provides a comprehensive fault monitoring system that will detect faults in the detection, activation, and siren circuits, and any malfunctions of the control panel's internal components.

Modules are available to allow for: extended or delayed system discharge or shutdown of devices.

## Specifications

<b>Dimensions</b>	148L x 84W x 35D mm
<b>Material</b>	Diecast Aluminium, UV Tolerant
<b>Ingress Protection</b>	IP65
<b>Operating Temp.</b>	-40 to 85 degrees Celsius
<b>Power</b>	12-30VDC

<b>Detection Zones</b>	2
<b>Detectors per Zone</b>	Max 30 Conventional Detectors Max 30 Manual Actuators
<b>Agent Release</b>	Thermal >80°C , NC, Non-resettable
<b>Siren Strobe</b>	Max 0.5A