



Amerex Corporation

RUGGED

- 5 Year Manufacturer's Warranty
- Stored Pressure Design
- Polished Stainless Steel Cylinders
- All Metal Valve Construction
- Exclusive crevice free, butt welded cylinders
- Temperature Range +40°F to 120°F

CLEAN

- Leaves no powder residue

USER FRIENDLY

- Maximum visibility during discharge
- Large Loop Stainless Steel Pull Pin
- Easy to recharge and maintain

APPLICATION

- Designed for use in manned pressure vessels/ hyperbaric chambers.
- Suitable for use in chambers simulating 225 ft. (depth)



Pressure Relief Valves

Model 240H



Model 240H utilizes the cooling, soaking and penetrating effect of a 45-55 ft. stream of WATER. The 55 sec. discharge time makes it very effective for inexperienced operators for use on Class A fires.

Protected by two safety relief valves for high and low pressure variations

AGENT TYPE	WATER
DESIGN	HOSE & NOZZLE
MODEL NUMBER	240H
CAPACITY	2.5 GAL
SHIPPING WT. (LBS. EMPTY)	7.5
HEIGHT (IN.)	24.5
WIDTH (IN.)	9
DEPTH (IN.)	7
RANGE (INITIAL- FT)	45-55
DISCHARGE TIME (SEC.)	55
INCLUDED BRACKET	WALL

ISO-9001 / ISO-14001 Certified

CONFORMS TO TEST STANDARDS:

WATER: CAN/ULC-S507 - ANSI/UL626 & CAN/ULC-S508 - ANSI/UL711

MADE IN U.S.A.

240H - WATER

