

CARBON DIOXIDE EXTINGUISHERS

Large volume CO2 protection in either 50 or 100 lb. (2-50 lb. cylinders) wheeled extinguishers. Rugged construction and easy to operate with a "quick-opening" 'T' handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and makes an excellent choice in settings that require a clean agent.

FEATURES

- Heavy-duty steel carriages
- Quick-opening brass valve
- Squeeze-grip chrome-plated discharge valve
- Reinforced wire-braided hose and shock-resistant horn to reduce static electricity
- Brass hose fittings
- UL/ULC label with QR code
- Large instruction pictogram
- DOT/TC cylinder with quick-opening brass valve
- Clean, non-contaminating odorless gas
- 5-Year Warranty



SPECIFICATIONS	CARBON DIOXIDE	
Model Number	333	334
Agent	Carbon Dioxide CO2	
U.L Rating	20B : C	
Capacity	22.7 kg	45.4 kg
Shipping Weight	116 kg	210 kg
Dimensions	1200 x 590 x 1220	
Discharge time Sec	44	74
Cylinder	DOT 3AA2015	
Discharge Range	3 - 5m	
Operating Temperature	-40°C to +49°C	
Hose Length	12.1 m	
Hose Diameter	127mm	
Wheels-Semi Pneumatic	410 x 102 mm	
USCG Approved	YES	

Ideal for Raised Platforms & Helidecks



OPTIONAL EQUIPMENT



Extension Lance
Ideal for Helidecks

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - UL 154 &
CAN/ULC-S508 - UL 711



Made in USA