

ABE DRY CHEMICAL

RUGGED

- 6-Year manufacturer's warranty
- Stored Pressure Design
- Dependable drawn steel cylindrs
- Durable high-gloss polyester powder paint
- All-metal valve construction
- Operating Temperature Range -65° to 120°F

BRASS VALVE - Heavy Duty

- Chrome Plated Brass valve body
- Stainless Steel handle & lever

ALUMINIUM VALVE – Light Duty

- Anodized aluminium valve body
- Anodized aluminium lever & handle

ABE or **MULTI-PURPOSE** extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface where it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.



ALUMINIUM VALVE RANGE



BRASS VALVE RANGE

AGENT TYPE	ABE DRY CHEMICAL POWDER						
Valve Type	Anodized Aluminum				Chrome-Plated Brass		
Model	417	500	456	411	424	419	423
AS Rating	1A:20B:E	2A:40B:E	4A:60B:E	6A:80B:E	2A:40B:E	4A:80B:E	6A:80B:E
UL Rating	1A:10B:C	2A:10B:C	4A:80B:C	10A:120B:C	2A:10B:C	4A:80B:C	10A:120B:C
Capacity kg	1.1	2.3	4.5	9	2.3	4.5	9
Ship Weight kg	2.5	4.3	8.2	17.7	8.2	8.6	17.7
Shipping Dims mm	394 x 146 x 76	387 x 184 x 108	508 x 197 x 127	680 x 200 x 200	394 x 203 x 106	450 x 241 x 152	680 x 200 x 200
Range m	3-5	4-6	5-7	5-7	4-6	4-6	5-7
Disch Time Sec	10	14	20	30	14	22	30
Oper Press psi	195	195	195	195	195	195	195
Incl Bracket	Vehicle	Vehicle	Wall		Vehicle	Wall	

CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - UL 299 &
CAN/ULC-S508 - UL 711

MANUFACTURED AND TESTED to UL STANDARDS

COMPLIES WITH NFPS 10 STANDARD
ISO 9001 / ISO 14001 CERTIFIED
UI LISTED



MADE in USA