

WATER & FOAM

RUGGED

- 5-Year manufacturer's warranty
- Store pressure design
- Stainless steel cylinder
- UV Rated Powder Coating
- All-metal valve construction
- Exclusive crevice-free, butt-welded cylinder
- Temperature range +40°F to 120°F

USER-FRIENDLY

- Maximum visibility during discharge
- Large Loop stainless steel pull pin



Model 240 utilises the cooling, soaking and penetrating effect of a 13-17m stream of WATER. The 60 sec. discharge time makes it very effective for inexperienced operators to use on Class A fires. Protect from Freezing by adding the Model 506 Stream/Anti-Freeze charge. In Western Australia, South Australia and other areas with a high level of chloride content water it must be corrosion protected by adding the Model 507 charge.

Model 250 AFFF FOAM Class A:B extinguisher. Easy and effective application with air aspirated nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

AGENT TYPE		Water	AFFF Foam
Model Number		240AS	250AS
Application		Hose and Nozzle	
U.L. Rating		2A	3A:20B
AS/NZ Rating		3A	3A:20B
Capacity		9.4 Litres	9.4 Litres
Shipping Wt (Empty)		3.4 Kg	5 Kg
Height	mm	620	620
Width	mm	230	230
Depth	mm	180	180
Range	m	13-17	3-4
Discharge time Sec		60	55
Standard Bracke		Wall Bracket	

CONFORMS TO TEST STANDARDS:

CAN/ULC-S507 - UL 626 &
CAN/ULC-S508 - UL 711

MANUFACTURED AND TESTED to UL STANDARDS

COMPLIES WITH NFPS 10 STANDARD
ISO 9001 / ISO 14001 CERTIFIED
UL LISTED



MADE in USA