



Quality is Behind the Diamond®

Amerex Corporation

Manufactured to
ANSI / UL Standards
AS & NZ Standards
ISO-9001 / ISO-14001 Certified

RUGGED

- Fully Drawn dependable Steel Cylinders
- No Weld Construction
- All Metal Valve Construction
- UV Rated Powder Coating
- Easy to Service and Maintain
- UL Listed
- Coast Guard Approved
- Temperature Range -53°C to 50°C
- Bar Coded Labels

STORED PRESSURE

ALUMINIUM VALVE RANGE



BRASS VALVE RANGE



AS & NZ Standards Have an Additional White ID Band



ABE or Multi-purpose extinguishers utilise a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 177°C and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Specifications		ABE Dry Chemical							
Valve Type		Aluminium				Brass Chrome Plated (No Alloy)			
Model		B417	B500	B456	A411AS	B424	419AS	668AS	423AS
Size & Capacity		1.1kg	2.3kg	4.5kg	9.0kg	2.3kg	4.5kg	6.0kg	9.0kg
Application		Nozzle	Hose and Nozzle			Hose and Nozzle			
AS/NZ Rating		1A:20B:E	2A:40B:E	4A:60B:E	6A:80B:E	2A:40B:E	4A:80B:E	4A:80B:E	6A:80B:E
U.L. Rating		1A:10B:C	2A:10B:C	4A:80B:C	20A:120B:C	2A:10B:C	4A:80B:C	-	20A:120B:C
SSL Listed				Yes	Yes				
F.M. Approved		Yes	Yes	Yes	Yes	Yes	Yes		Yes
Shipping Wt Kg.		2.4 / 2.5	4.2 / 4.3	8.2	17.7	8.2	8.6	11.0	17.7
Height	mm	394	387	508	591	394	450	550	607
Width	mm	146	184	197	273	203	241	230	260
Depth	mm	76	108	127	178	108	152	152	178
Range	m	3 - 5	4 - 6	5 - 7	5 - 7	4 - 6	4 - 6	5 - 7	5 - 7
Chrome Plated Cyl.		Yes	Yes	Yes					
Corrosion Paint						Yes		Yes	Yes
Disch. Time Sec		10	14	20	30	14	22	26	30
Std Bracket		Wall / Vehicle-Marine				Wall			