



Quality is Behind the Diamond®
Amerex Corporation

Manufactured to
 ANSI / UL Standards
 AS & NZ Standards
 ISO-9001 / ISO-14001 Certified

RUGGED

- Rust Free Aluminium Cylinders
- All Metal Valve Construction
- Durable High Gloss Polyester Coating
- Easy to Service and Maintain
- UL Listed
- Coast Guard Approved
- Temperature Range -30°C to 50°C
- Bar Coded Labels



Carbon Dioxide is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

SPECIFICATIONS

Model Number	322	330	331	332	
Size & Capacity	Lbs	5	10	15	20
Application		Horn	Hose & Horn	Hose & Horn	Hose & Horn
U.L. Rating		5B : C	10B : C	10B : C	10B : C
Shipping Weight	kg	6.4	12.8	17.1	23
Height	mm	450	610	760	760
Width	mm	210	305	305	330
Depth	mm	135	180	180	205
Range	m	1 - 3	1 - 3	1 - 3	1 - 3
Discharge time Sec		10	10	12.5	19
Standard Bracket	Wall Bracket				

CARBON DIOXIDE CO2

