



Quality is Behind the Diamond®

Amerex Corporation

Manufactured to
ANSI / UL Standards
AS & NZ Standards
ISO-9001 / ISO-14001 Certified

RUGGED

- Dependable Steel Cylinders
- Stored Pressure design
- All Metal Valve Construction
- UV Rated Powder Coating
- Leaves no Residue
- UL Listed
- Maximum visibility during discharge
- Temperature Range -53°C to 50°C
- Durable polyester Powder Coated

Use of Halon is restricted in Australia special licenses are required.



344

352

355

354



369

371

361



HALON 1211 is a liquified gas, pressurized with nitrogen, which discharges as a vapor causing no cold or static shock and no impairment of the operator's vision. This "CLEAN" agent quickly penetrates difficult to see and hard to reach areas and leaves no residue. It is recommended for protection of delicate, sensitive and expensive computers, electrical equipment, tapes and film, automotive and aircraft engines, laboratory chemicals and equipment.

Quality industrial grade hardware, "CLEAN" agent, light weight, good discharge range and excellent fire extinguishing ability.

Specifications	ALUMINIUM VALVE				BRASS VALVE-Chrome Plated		
Model	B394TS	C352TS	C354TS	B355T	B369	B371	B361
Size & Capacity kg	0.6	1.1	1.4	2.3	4	5.9	7.8
Applicator	Nozzle	Nozzle	Hose	Nozzle	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle
U.L Rating	2B : C	5B : C	5B : C	10B : C	10B : C	2A: 40B : C	4A : 80B : C
Shipping Weigl kg	1.25	2.5	2.7	4.4	7.6	10	16.5
Dimensions mm	250 x 90 x 70	360 x 115 x 75	360 x 150 x 75	380 x 145 x 110	410 x 210 x 125	510 x 210 x 125	600 x 245 x 175
Range m	3 - 4	3 - 5	3 - 5	3 - 5	4 - 6	4 - 6	4 - 6
Minimum Spac. m ³	4.4	8.8	10.6	17.7	31.8	45.9	60
Std Bracket	Vehicle	Aircraft	Aircraft	Vehicle	Wall	Wall	Wall

HALON 1211

