



Quality is Behind the Diamond®

Amerex Corporation

Manufactured to
ANSI / UL Standards
AS & NZ Standards
ISO-9001 / ISO-14001 Certified

RUGGED

- Dependable Steel Cylinders
- Stored Pressure design
- All Metal Valve Construction
- UV Rated Powder Coating
- Leaves no Residue
- UL Listed
- Maximum visibility during discharge
- Temperature Range -53°C to 50°C
- Durable polyester Powder Coated



384

385

386

394

397

398



HALOTRON I is a “Clean Agent” HydroChloroFluoroCarbon discharged as a rapidly evaporating liquid which leaves no residue. It effectively extinguishes Class A and B fires by cooling and smothering. Halotron is pressurized with Argon gas and is an EPA and FAA approved HCFC blend B agent approved for use on Class A, B and C fires. It has a low GWP, and a low Atmospheric Lifetime. In Australia Halotron is approved by CASA as an acceptable replacement for Halon 1211 extinguishers in aircraft. Recommended install Model B385TS 1.1Kg with double strap bracket.

Halotron is intended for use in areas formerly protected by Halon 1211 extinguishers such as computer rooms, telecommunications facilities, clean rooms.

Specifications	ALUMINIUM VALVE				BRASS VALVE-Chrome Plated		
Model	A384T	B385TS	B386T	B394TS	397	398	
Size & Capacity	kg	0.6	1.1	2.3	2.5	5	7
Applicator	Nozzle				Hose & Nozzle		
U.L Rating	1B : C	2B : C	5B : C	5B : C	1A: 10B : C	2A : 10B : C	
Shipping Weight	kg	1.5	2.4	4.2	4.6	10.3	12.5
Dimensions	mm	250 x 90 x 75	390 x 140 x 75	380 x 145 x 110	380x x130 x 110	540 x 230 x 150	540 x 230 x 150
Range	m	2 - 3	2 - 3	3 - 5	3 - 5	3 - 5	4 - 6
Disch. Time Sec		9	9	9	9	9	14
Std Bracket		Aircraft	Aircraft	Aircraft	Aircraft	Wall Bracket	

HALOTRON™ I