



Quality is Behind the Diamond®

Amerex Corporation

Manufactured to
ANSI / UL Standards
AS & NZ Standards
ISO-9001 / ISO-14001 Certified

RUGGED

- High Grade Stainless Steel Cylinders
- Durable high gloss Polyester Powder coat paint
- All Metal Valve Construction
- Tested on Commercial deep fat fryers using ANSI / U.L. test Protocol
- Swivel Hose connection allows nozzle orientation for an overhead application
- Shorter discharge hose making it easier to use in small confined space cooking areas
- Nozzle grip design with 45° angle for easy application
- Low PH Wet Chemical agent
- Agent discharged as fine mist prevents grease splash and re-flash.
- Precise extinguishing agent application - no dry chemical to clean up
- Excellent for use on all cooking appliances including solid fuel charbroilers
- Tested to ANSI / UL 71 and safe to use on Class C Fires
- Bar Coded Labels
- 5 Year Manufacturers Warranty
- U.L. Listed



STORED PRESSURE



WET CHEMICAL

WET CHEMICAL extinguishers are the best restaurant kitchen appliance hand portable fire extinguishers you can purchase. Both have been tested and approved for Class F specifically for kitchen hazards. They contain a special potassium acetate based, low PH agent developed for use in pre-engineered restaurant kitchen systems. The recent trend to more efficient cooking appliances and use of unsaturated cooking oils dictates the use of a hand portable fire extinguisher with greater fire fighting capacity and cooling effect to combat these very hot and difficult fires. Available in two sizes - 6 litre or 9 litre with attractive stainless steel cylinders and easy to use spray and hose application nozzle. The superior fire fighting capability of the Wet Chemical agent is placed exactly where you aim it with no residue to clean up. The models 260 and B262 are the ideal "kitchen use" fire extinguishers.

SPECIFICATIONS		WET CHEMICAL	
Model Number		260AS	B262
Application		Hose & Spray Nozzle	
Agent		POTASSIUM ACETATE MIXED WITH WATER	
AS/NZ Rating		2A : 4F	-
SSL Listed		Yes	Yes
U.L Rating		2A : K	2A : K
Capacity		6 Litres	9 Litres
Shipping Wt (Empty)		7.9kg	9.1kg
Height	mm	485	620
Width	mm	230	230
Depth	mm	180	180
Range	m	3 - 4	3 - 4
Discharge time Sec		54	80
Standard Bracket		Wall Bracket	

