

Dry Chemical Powder Fire Extinguishers are suitable for fighting class A,B and E fires. ABE powder extinguishers have a very good firefighting capacity.

Features:

- Drawn Cylinder – Reduced Neck Problems
- Large High-Quality Gauge
- Rugged Construction
- Powder Coat Finish
- UV Rated Paint
- Pull Ring Retainer fitted on all units
- Hose Retainer fitted on all units
- 85% MAP ABE Powder
- AS/NZ Standard Approved



| MODEL | | 110 | 120 | 150 | 250 | 450 | 900 |
|--------------------|----|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Size | | 1.0kg | 1.0kg | 1.5kg | 2.5kg | 4.5kg | 9.0kg |
| AS / NZ Rating | | 1A:10B:E | 1A:20B:E | 2A:30B:E | 3A:40B:E | 4A:60B:E | 6A:80B:E |
| Applicator | | Nozzle | | Hose & Horn | | | |
| Standard Bracket | | Plastic Vehicle | Metal Vehicle | | Vehicle & Wall | Wall | Wall |
| Mass Full | kg | 1.7 | 1.7 | 2.5 | 4.2 | 7.3 | 13.6 |
| Specifications | | | | | | | |
| Cylinder Diameter | mm | 80 | 80 | 90 | 120 | 145 | 180 |
| Cylinder Height | mm | 300 | 300 | 360 | 415 | 525 | 590 |
| Discharge Time | | 11 sec | 11 sec | 13 sec | 17 sec | 17 sec | 28 sec |
| Operating Pressure | | 1000 kPa | | | | 1500 kPa | |
| Test Pressure | | 2500 kPa | | | | | |
| Shipping | | | | | | | |
| Master Carton | | | | | | | |
| Contents | | 6 Units | 6 Units | 4 Units | 4 Units | 1 Unit | 1 Unit |
| Weight | | 12.0 kg | 12.3 kg | 12.1 kg | 20.2 kg | | |
| Dims L x W x H | mm | 335 x 280 x 340 | 300 x 280 x 340 | 270 x 270 x 380 | 335 x 340 x 450 | | |
| Unit | | | | | | | |
| Weight | kg | 1.89 | 1.98 | 2.92 | 4.87 | 7.85 | 14.26 |
| Dims L x W x H | mm | 105 x 135 x 320 | 95 x 135 x 320 | 125 x 125 x 365 | 155 x 165 x 430 | 160 x 170 x 560 | 210 x 200 x 620 |