

Carbon Dioxide is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

Features:

- Light weight Alluminium cylinders
- Brass valve assembly
- Hose & horn on 3.5kg & 5kg models
- Horn on the 2kg model
- Rugged Epoxy coated finish
- Stainless Steel handle & lever
- Rugged Construction
- UV rated paint work 2 years
- AS / NZ Standard Approved



MODEL		E-204	E-354	E-504
Size		2.0 kg	3.5 kg	5.0 kg
AS / NZ Rating		2B : E	5B : E	5B : E
Applicator		Nozzle	Hose & Horn	
Standard Bracket		Wall		
Specifications				
Mass Full	kg	5.2	9.0	12.0
Cylinder Diameter	mm	112	140	152
Cylinder Height	mm	525	570	660
Discharge Time		12 sec	12 sec	14 sec
Effective Range	m	1-1.5	1-2	1-2
Test Pressure	mPa	25	25	25
Shipping				
Weight	kg	5.5	9.9	12.7
Dims L x W x H	mm	545 x 180 x 120	595 x 260 x 140	690 x 300 x 165