

Ecco Fire Extinguishers

Ecco
Portable
Fire Equipment



- ABE Dry Chemical Powder Extinguishers
- Water and Foam Extinguishers
- CO2 Extinguishers
- Wet Chemical Extinguishers
- Wheeled Extinguishers
- SOLAS Approved Units



Ecco

Dry Chemical Extinguishers

Ecco
Portable
Fire Equipment



Product Features:

- Drawn Cylinder – Reduced Neck Problems
- Large High Quality Gauge
- Rugged Construction
- Powder Coat Finish
- UV Rated Paint
- Pull Ring Retainer fitted on all units
- Hose Retainer fitted on all units
- 85% MAP ABE Powder
- AS/NZ Standard Approved



ABE—Extinguishers

MODEL		110	120	150	250	450	900
Size		1.0kg	1.0kg	1.5kg	2.5kg	4.5kg	9.0kg
AS / NZ Rating		1A:10B:E	1A:20B:E	2A:30B:E	3A:40B:E	4A:60B:E	6A:80B:E
Activ Fire Listed		Yes	Yes	Yes	Yes	Yes	Yes
Applicator		Nozzle		Hose & Horn			
Standard Bracket		Plastic Vehicle	Metal Vehicle		Vehicle & Wall	Wall	Wall
Shipping Specifications							
Master Carton Contents		6 Units	6 Units	4 Units	4 Units	1 Unit	1 Unit
Weight . Per Unit	kg	1.89	1.98	2.92	4.87	7.85	14.26
Weight . Master Carton	kg	12.0 kg	12.3 kg	12.1 kg	20.2 kg		
Dimensions . Unit	LxWxH mm	105 x 135 x 320	95 x 135 x 320	125 x 125 x 365	155 x 165 x 430	160 x 170 x 560	210 x 200 x 620
Dimensions . Master Ctn	LxWxH mm	335 x 280 x 340	300 x 280 x 340	270 x 270 x 380	335 x 340 x 450		
Product Specifications							
Mass Full	kg	1.7	1.7	2.5	4.2	7.3	13.6
Cylinder Diameter	mm	80	80	90	120	145	180
Cylinder Height	mm	300	300	360	415	525	590
Discharge Time	Sec.	11 sec	11 sec	13 sec	17 sec	17 sec	28 sec
Operating Pressure		1000 kPa				1500 kPa	
Test Pressure		2500 kPa					

Ecco

CO2 Extinguishers

Ecco
Portable
Fire Equipment



Product Features:

- Lightweight Alloy Steel Cylinders
- Chrome Plated Brass Valve Assembly
- Hose and Horn on 3.5kg & 5kg Models
- Swing Arm Fold Away Horn on 2kg Model
- Rugged Epoxy Coated Finish
- Stainless Steel Handle & Lever
- Rugged Construction
- UV Rated Paint Work
- AS/NZ Standard Approved



CO2 Extinguishers

Specifications				
Model		E-204	E-354	E-504
Size		2.0 kg	3.5 kg	5.0 kg
AS / NZ Rating		2B : E	5B : E	5B : E
Shipping Specifications				
Shipping Weight	kg	6.5	10.3	13.7
Height	mm	580 x 190 x 140	630 x 180 x 140	760 x 180 x 140
Width	mm	190	180	180
Length	mm	140	140	140
Product Specifications				
Mass Full	kg	6.32	9.97	13.28
Cylinder Diameter	mm	100	136	136
Effective Range	m	1-1.5	1-2	1-2
Discharge Time	Sec	12	12	14
Test Pressure	mPa	25.0	25.0	25.0

Ecco

Foam & Water Extinguishers

Ecco
Portable
Fire Equipment



Product Features:

- Stainless Steel Cylinders Painted
- Stainless Steel Handles
- Brass Chrome Plated Valve
- Large High Quality Gauge
- Schroeder Valve for ease of charging
- Wall Mounting Bracket included
- Stainless Steel Skirt for protection to base
- Pull Ring Retainer
- Powder Coat Finish with UV Rated Paint
- AS/NZ Standard Approved

Foam & Water Extinguishers

Specifications			
Model		941	902
Size		9.4 Lit	9.0 Lit
Agent		Water	AFFF
AS / NZ Rating		3A	3A : 20B
Shipping Specifications			
Shipping Weight	kg	3.8	4.5
Height	mm	675 x 200 x 200	675 x200 x 200
Product Specifications			
Mass Full	kg	13.0	12.6
Cylinder Diameter	mm	180	180
Height	mm	580	580
Operating Pressure	kPa	690	690
Test Pressure	kPa	2500	2500



Ecco

Wet Chemical Extinguishers

Ecco
Portable
Fire Equipment



Product Features:

- Stainless Steel Cylinders Painted
- Stainless Steel Handles
- Brass Chrome Plated Valve
- Large High Quality Gauge
- Precise Extinguishing Agent application
- Wall Mounting Bracket included
- Excellent for use on all cooking appliances
- Pull Ring Retainer
- Hose Retainer fitted
- Low pH Agent (pH Level 8.2)
- Powder Coat Finish with UV Rated Paint
- AS/NZ Standard Approved



Wet Chemical Extinguishers

Specifications

Model		313
Size		3.0 Lit
AS / NZ Rating		1A : 3F
Shipping Specifications		
Shipping Weight	kg	5.3-
Height	mm	440 x 160 x 140
Product Specifications		
Mass Full	kg	5.1
Cylinder Diameter	mm	140
Height	mm	340
Operating Pressure	kPa	690
Test Pressure	kPa	2500

Ecco

Spray Foam Extinguishers

Ecco
Portable
Fire Equipment



Product Features:

- Stainless Steel Cylinders Painted
- Stainless Steel Handles
- Brass Chrome Plated Valve
- Large High Quality Gauge
- Precise Extinguishing Agent application
- Wall Mounting Bracket included
- Excellent for use on all cooking appliances
- Pull Ring Retainer
- Hose Retainer fitted
- Low pH Agent (pH Level 8.2)
- Powder Coat Finish with UV Rated Paint
- AS/NZ Standard Approved



Wet Chemical Extinguishers

Specifications			
Model		212	302
Size		2.1 L	3.0 L
Agent		AFFF	
AS / NZ Rating		1A:5B:1F	2A:5B:2F
Shipping Specifications			
Shipping Weight	Kg	1.9	2.2
Dimensions	mm	525 x 130 x 120	440 x 155 x 170
Product Specifications			
Mass Full	Kg	3.8	5.1
Cylinder Diameter	mm	100	140
Height	mm	500	340
Operating Pressure	kPa	1030	690
Test Pressure	kPa	2500	2500

Ecco Wheeled Extinguishers

Ecco
Portable
Fire Equipment

Certified Product - AS 4265
Global-Mark.com.au®
ID Number: 103334



Product Features :

- Stainless Steel Cylinder Painted
- Brass Valve with Lever Action and Pressure Release Valve
- Alloy Nozzle with SS Ball Valve for Operation.
- Large High Quality Gauge - 1050kPa
- High Quality Rugged Trolley
- 8 Metre Hose for direct discharge
- Hose Retainer for support & Hinged Support Frame
- Rugged Construction
- 400mm Solid Foam Filled Tyres with Bearings for easy movement
- Hassle free, easy recharge
- Powder Coat Finish with UV Rated
- Up to 12m Discharge
- AS/NZ Standard Approved



Size	Part No.	Rating	Description	Mass Empty	Width mm	Height mm
50-100 Lit.	E-M100	3A : 20B	Wheeled Foam Extinguisher	63 kg	680	1280