

RE-HEALING™ RF3, 3% FOAM CONCENTRATE

CONCENTRATES



Description

RE-HEALING™ RF3 foam concentrate from SOLBERG® is an innovative environmentally sustainable fluorosurfactant and fluoropolymer-free foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires. Proportioned at 3% solution, RE-HEALING RF3 foam concentrate can be used in fresh, salt or brackish water. RE-HEALING RF3 foam possesses excellent burn back resistance due to its remarkable flow and rapid resealing characteristics. RE-HEALING foam concentrates are formulated using a new high performance synthetic foam technology to replace traditional AFFF, FFFP foam concentrates and older protein and fluoroprotein foams. RE-HEALING RF3 foam concentrate contains no sediments.

Application

RE-HEALING RF3 foam concentrate is intended for use on Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam concentrate can be used to prevent re-ignition of a liquid spill and control hazardous vapors. On Class A fuels, RE-HEALING RF3 foam concentrate

will improve extinguishment in deep-seated fires. Foam non-air aspirating discharge devices as well as air aspirating discharge devices, including standard sprinkler heads, can be used to obtain maximum results. The product is mixed 3 part foam concentrate to 97 parts water. It may also be used as a 3% pre-mix solution. RE-HEALING RF3 foam concentrate is compatible with most dry powder (chemical) agents.

Performance

Fire Performance

RE-HEALING RF3 foam concentrate has been tested to and meets the fire performance test criteria of Underwriters Laboratories, Inc. (UL) Standard 162 (latest edition), European Standard EN 1568 Part 3 and International Civil Aviation Organization (ICAO) Level B.

Foam Proportioning

RE-HEALING RF3 foam concentrate can be proportioned at the proper foam solution percentage using common foam proportioning devices such as:

- Eductors
- Inline balanced pressure proportioners
- Ratio controllers
- Self-educing nozzles

Typical Physical Properties at 77° F (25° C)

Appearance:	Brown liquid
Freezing Point:	23° F (-5° C) <i>(No quality loss after thawing)</i>
Maximum storage temp:	120° F (49° C)
pH:	7.0 - 8.0
Refractive index:	1.3865 - 1.3869
Specific gravity:	1.062 - 1.066
Viscosity:	4900 - 5300 cP*
Sediments:	None

*Brookfield Viscometer Spindle #4, Speed 30

Storage

The minimum and maximum temperature for RE-HEALING RF3 foam concentrate is 35° F to 120° F (1.7° C to 49° C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 10 years.

Compatibility

RE-HEALING RF3 foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing, consult Solberg Technical Services.

Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. www.solbergfoam.com



**Materials of
Construction Compatibility**

RE-HEALING RF3 foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about materials of construction compatibility, consult Solberg Technical Services.

Inspection

RE-HEALING RF3 foam concentrate or pre-mix solution should be inspected annually per National Fire Protection Association (NFPA)

Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

Environmental Information

RE-HEALING foam concentrates are fluorosurfactant, fluoropolymer-free products for use on Class B hydrocarbon fuels with no environmental concerns for persistence, bioaccumulation or toxic break down.

Approvals & Listings

SOLBERG manufactured products are thoroughly inspected and undergo

rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

RE-HEALING RF3 foam concentrate is Underwriters Laboratories, Inc. Listed in accordance with UL 162 (Standard for Safety for Foam Equipment and Liquid Concentrates), European Standard EN 1568 Part 3 and International Civil Aviation Organization (ICAO) Level B certified.

Ordering Information

RE-HEALING RF3 foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	SHIPPING WEIGHT	CUBE
20020	RE-HEALING RF3, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
20021	RE-HEALING RF3, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
20022	RE-HEALING RF3, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)
20023	RE-HEALING RF3, bulk	Call Customer Services	

SOLBERGFOAM.COM

FORM NUMBER F-2013005-1

COPYRIGHT © 2013. ALL RIGHTS RESERVED.
SOLBERG® AND RE-HEALING™ ARE TRADEMARKS
OF THE SOLBERG COMPANY OR ITS AFFILIATES.

AMERICAS
THE SOLBERG COMPANY
1520 Brookfield Avenue
Green Bay, WI 54313
USA
Tel: +1 920 593 9445

EMEA
SOLBERG SCANDINAVIAN AS
Radøyvegen 721 - Olsvollstranda
N-5938 Sæbøvågen
Norway
Tel: +47 56 34 97 00

ASIA-PACIFIC
SOLBERG ASIA PACIFIC PTY LTD
3 Charles Street
St. Marys NSW 2760
Australia
Tel: +61 2 9673 5300