



RE-HEALING™ RF3X6% ATC™ FOAM CONCENTRATE CONCENTRATES



Description

RE-HEALING™ RF3x6 ATC foam concentrate from SOLBERG® is an innovative environmentally sustainable fluorosurfactant and fluoropolymer-free foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires at 3% and polar solvent fuel fires at 6% solution. RE-HEALING RF3x6 ATC foam can be used in fresh, salt or brackish water. RE-HEALING RF3x6 ATC foam possesses excellent burn back resistance due to its remarkable flow and rapid resealing characteristics. RE-HEALING foam concentrates are formulated using a new high performance synthetic foam technology to replace traditional AFFF, FFFP foam concentrates and older protein and fluoroprotein foams.

Application

RE-HEALING RF3x6 ATC foam concentrate is intended for use on Class B hydrocarbon or polar solvent fuel fires. The foam can be used to prevent re-ignition of a liquid spill and control hazardous vapours. On Class A fuels, RE-HEALING RF3x6 ATC foam concentrate will improve extinguishment in deep-seated fires. Foam discharge devices such as non-air aspirating, as well as, air aspirating equipment, including standard sprinkler heads, can

be used to obtain maximum results. The product is mixed 3 parts foam concentrate to 97 parts water for hydrocarbon fuels or 6 parts foam concentrate to 94 parts water for polar solvent fuels. It may also be used as a pre-mix solution. RE-HEALING RF3x6 ATC foam concentrate is compatible with most dry powder (chemical) agents.

Performance

Fire Performance

RE-HEALING RF3x6 ATC foam concentrate has been tested to and meets the fire performance test criteria of European Standard EN 1568 Part 3 & 4 and International Civil Aviation Organization (ICAO) Level B and Level C.

Foam Proportioning

RE-HEALING RF3x6 ATC foam concentrate can be proportioned at the proper foam solution percentage using common foam proportioning devices such as:

- Eductors
- Inline balanced pressure proportioners
- Ratio controllers
- Self-educing nozzles

Typical Physical Properties at 25° C (77° F)

Appearance:	Brown liquid
Freezing Point:	-5° C (23° F) <i>(No quality loss after thawing)</i>
Maximum storage temp:	49° C (120° F)
pH:	7.0 - 8.5
Refractive index:	1.3750 - 1.3850
Specific gravity:	1.050 - 1.085
Viscosity:	4300 -5900 cP*
Sediments:	None

**Brookfield Viscometer Spindle #4, Speed 30*

Storage

The minimum and maximum temperature for RE-HEALING RF3x6 ATC foam concentrate is 1.7° C to 49° C (35° F to 120° F).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

Compatibility

RE-HEALING RF3x6 ATC foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing, consult Solberg Technical Services.

Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. www.solbergfoam.com



Materials of Construction Compatibility

RE-HEALING RF3x6 ATC foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about materials of construction compatibility, consult Solberg Technical Services.

Inspection

RE-HEALING RF3x6 ATC foam concentrate or pre-mix solution should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25.

A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

Environmental Information

RE-HEALING foam concentrates are fluorosurfactant, fluoropolymer-free products for use on Class B hydrocarbon fuels with no environmental concerns for persistence, bioaccumulation or toxic break down.

Certifications

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the

finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

RE-HEALING RF3x6 ATC foam concentrate is Approved to European Standard EN 1568 Part 3 & 4 and International Civil Aviation Organization (ICAO) Level B (3%, 6% solutions) and Level C (6% solution).

Ordering Information

RE-HEALING RF3x6 ATC foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	APPROXIMATE SHIPPING WEIGHT	APPROXIMATE CUBE
20030	RE-HEALING RF3x6 ATC, 20 litre (5 gallon) pail	21 kg (45 lb)	0.04 m ³ (1.25 ft ³)
20031	RE-HEALING RF3x6 ATC, 200 litre (55 gallon) drum	224 kg (495 lb)	0.33 m ³ (11.83 ft ³)
20032	RE-HEALING RF3x6 ATC, 1000 litre (265 gallon) tote	1118 kg (2465 lb)	1.42 m ³ (50.05 ft ³)
20033	RE-HEALING RF3x6 ATC, bulk	Call Customer Services	